

[WWW.CARTERCHAMBERS.COM](http://WWW.CARTERCHAMBERS.COM)

RENTAL FILTRATION EQUIPMENT

<b>MANUFACTURER</b>	OIL FILTRATION SYSTEMS
<b>CARTER CHAMBERS UNIT #</b>	VDOPS-15-N4-1
<b>MODEL #</b>	VDOPS-15VFD-840X-32KW-480-N4-B
<b>SERIAL #</b>	0022607-01
<b>MATERIALS</b>	CARBON STEEL
<b>ASME CODE</b>	NONE
<b>MAWP</b>	INLET - 28" Hg VACUUM TO +50 PSIG/OUTLET - 100 PSIG
<b>MAWT</b>	200 DEG. F.
<b>INLET CONNECTION</b>	1-1/2" CAM LOCK
<b>OUTLET CONNECTION</b>	1-1/2" CAM LOCK
<b>TEMPERATURE CONTROLS</b>	RELAY
<b>SYSTEM CONTROLS</b>	SIEMANS PLC
<b>MEASUREMENTS (OAWxOALxOAH)</b>	55" X 37" X 85"
<b>WEIGHT (LBS.)</b>	2800
<b>INTERIOR COATING</b>	SILVER RUST GRIP COATING
<b>EXTERIOR COATING</b>	ENAMEL
<b>SKID TYPE</b>	BUILT IN CASTERS, 2 WAY FORK
<b>VACUUM PUMP</b>	42.4 CFM INTERNALLY LUBRICATED CLAW
<b>CONDENSER</b>	AIR COOLED
<b>ELECTRICAL CLASSIFICATION</b>	NEMA 4
<b>ELECTRICAL REQUIREMENTS</b>	480V, 3 PHASE, 60 Hz
<b>INLET OIL HEATER - SELECTABLE</b>	32Kw LOW WATT DENSITY
<b>INLET STRAINER</b>	20 MESH
<b>DISCHARGE FILTER</b>	OPTIONAL
<b>FLOW RATING</b>	MAX 15 GPM, MINIMUM 3.8 GPM VARIABLE FREQUENCY DRIVE



<b>UNIT TYPE</b>	VACUUM DEHYDRATION SYSTEM
------------------	---------------------------